


FLAIL MOWERS





**WE
DEVELOPED
A COMPLETE
SYSTEM,
BECAUSE
HAVING
THE BEST
STEEL ISN'T
ENOUGH
FOR US.**

The “ALPEGO INSIDE” label, seen on all our machines, certifies the **exceptional quality** of Alpego products. A perfect combination of **top quality raw materials**, a **sustainable painting process** and **certified welding**; all to **guarantee exceptional lifetime and lasting quality**.



HIGH STRENGTH STEEL

All Alpego machines use **the best Swedish steel** to **reduce weight and enhance working performance**, minimising both fuel use and operating costs. This also has a huge impact on environmental sustainability.



ECO PAINTING

In Europe, this unique system allows every component to be **painted according to the most suitable process, while protecting the environment**. The system uses water-based and powder paints **with no production of VOC** (volatile organic compounds) emissions.



CERTIFIED WELDING

The exceptional durability of Alpego structural components has been guaranteed for over twenty years by the effectiveness of the **welds, that meet the standardised processes certified by the National Welding Institute**.

A complete range for every need

Three types of flail mower for a complete range up to 3.2 m.

The Alpego range of flail mowers meets the greatest professional needs of farmers and outsourcers looking for lasting, high-performance machines with unique technical solutions on the market.

The range includes: TRISAR multi-purpose flail mowers, TRILAT lateral flail mowers, TRISTOC shredders.

TRISAR

TR27

Multi-purpose flail mower
Rear mounted
HP 40-100
Pag. 10



TR36

Multi-purpose flail mower
Rear mounted
HP 45-120
Pag. 12



TR56

Multi-purpose flail mower
Rear mounted
HP 70-150
Pag. 12



TB2

Lowered multi-purpose flail mower
Rear mounted
HP 40-105
Pg. 8-9



TR27 F

Front-mounted multi-purpose flail mower
HP 40-100
Pag. 11




TR36 F

Multi-purpose flail mower
Front/rear mounted
HP 55-150
Pag. 13



TR56 F

Multi-purpose flail mower
Front/rear mounted
HP 75-180
Pag. 13



TRILAT

TL50

Heavy-duty lateral flail mower
HP 100-220
Pag. 18



TT97

Shredder
HP 80-160
Pag. 21



TL31

Lateral flail mower
HP 55-130
Pag. 16



TL33

Lateral flail mower
HP 55-130
Pag. 17



TRISTOC

"SSA" mulching chamber

The whole range of ALPEGO flail mowers is equipped with the exclusive "SSA" MULCHING CHAMBER

"We have been designing solutions to guarantee high mulching for years. The result is our SSA "Super Shredder Alpego" system, the mulching chamber suited to all conditions for both plant waste and wood residues."

Matteo Zambon
Technical Dept. Manager




TRISAR

Range of multi-purpose flail mowers

Alpego multi-purpose flail mowers are ideal for working in all situations with excellent results and in complete safety; for cutting grass, mulching prunings and wood residues in vineyards and orchards.


"SSA" MULCHING CHAMBER

Multi-purpose SSA "Super Shredder Alpego" mulching chamber (patented in Italy) with variable volume; changing the position of the inside hood, 2 different types of work can be obtained.



1 GRASS FUNCTION

The deflector on the hood remains open, for simple cutting and discharge after the roller (grass cuttings, bushes, thick vegetation).




2 FUNCTION FOR WOOD TURBO-MULCHER

The deflector on the hood remains low and the wood residues are finely mulched, remaining in the chamber until completely mulched (vines, brushwood, prunings, wood).



SIDE SHIFT

The Alpego flail mower side shift can be controlled manually or hydraulically.



REINFORCED ROTOR

The distinctive reinforced rotor fitted with oversized hammers delivers high centrifugal force for outstanding performance. The small gap between rotor and rear roller means that even large volumes of shredded product are always discharged effectively, preventing troublesome blockages.



SELF-CLEANING REAR ROLLER

The self-cleaning rear roller has an automatic roller cleaning system, thanks to its position very close to the rotor.



DOUBLE COUNTER-BLADE

The largest models in the Trisar range are equipped with a second counter-blade as standard. (TR36-TR56)



INTERNAL COUNTER-FRAME

The mulching chamber, consisting of a double metal frame, increases the strength and integrity of the machine, while protecting the rear hood against damage.



DOUBLE 3-POINT HITCH

The double 3-point hitch on the TR36F/TR56F ensures both front and rear applications on the machine.



Lowered multi-purpose flail mower for tractors up to 105 HP, working width from 2 m

Thanks to the patented SSA system, the TB2 lowered profile flail mower provides excellent results on grass, woody material, straw, plant residues, shrubs and prunings. It is also particularly recommended for vineyard maintenance.



VBHP SPECIAL BELT

The use of the new high-performance VBHP SPECIAL (V-Belt-High-Performance) belts offers retracting side transmission with narrow guard, ensuring high reliability.



	TB2-140	TB2-160	TB2-180	TB2-200
Working width (mm)	1400	1600	1800	2000
Transport width (mm)	1550	1750	1950	2150
Tractor power (HP)	40-105	45-105	50-105	55-105
Hammers (no.)	12	14	16	16
Belts (no.)	3	3	3	3
Roller diameter (mm)	140	140	140	140
Maximum cutting diameter (Ø cm)	5	5	5	5
Weight (Kg)	510	540	580	640

1 "SSA" MULCHING CHAMBER
Multi-purpose mulching chamber with variable volume and innovative crank control. Changing the position of the hood, 2 different types of work can be obtained.

2 INTERNAL COUNTER-FRAME
Mulching chamber with double metal frame to increase the strength and integrity of the machine.

3 SIDE SHIFT
Hydraulically controlled side shift with optimised central positioning.

4 BEVELLED FRAME
Frame with RH bevelled side with no jutting parts and inner rotor supports.

5 REAR ROLLER
The self-cleaning rear roller has an automatic roller cleaning system, thanks to its position very close to the rotor.

6 HIGH-TENSILE STEEL FRAME
Sturdy frame in dual-layer high-tensile steel.

7 CENTRAL GEARBOX
Concept of gearbox with a super-lowered design.

8 SIDE TRANSMISSION
Retracting side transmission with narrow guard, thanks to the use of the new high-performance distribution belts VBHP SPECIAL (V-Belt-High-Performance).


9 PROFESSIONAL ROTOR
Professional rotor with angled tool-holder grips equipped with large self-sharpening universal Hammers with M18 bolts.

EQUIPMENT
PTO 540 rpm / Linkage cat. 1 and 2N / Drive shaft with guard / Rear roller Ø140 mm with protected bearings / Fixed counter-blade / Hydraulic side shift.

TR27

Multi-purpose flail mower
for tractors up to 105 HP,
working width up to 2 m

Thanks to the patented SSA system, the TR27 multi-purpose flail mower provides excellent results on grass, woody material, straw, crop residues, shrubs and prunings. It is also ideal for tending fallow land and green areas.



	TR27-140	TR27-160	TR27-180	TR27-200
Working width (mm)	1400	1600	1800	2000
Transport width (mm)	1550	1750	1950	2150
Tractor power (HP)	40-105	45-105	55-105	55-105
Hammers (no.)	12	14	16	16
Belts (no.)	3	3	3	3
Roller diameter (mm)	140	140	140	140
Maximum cutting diameter (Ø cm)	6	6	6	6
Weight with mechanical side shift (Kg)	515	545	595	630
Weight with hydraulic side shift (Kg)	520	550	600	635

1 "SSA" MULCHING CHAMBER

Variable volume mulching chamber with manual control for adjustment of the inside mobile gate.

2 SIDE TRANSMISSION

Side transmission with narrow casing thanks to the use of new high-performance VBHP SPECIAL (V-Belt-High-Performance) distribution belts.

3 SIDE SHIFT

Mechanic or hydraulic side shift (CHOOSE WHICH).

4 PROFESSIONAL ROTOR

Professional rotor with angled tool-holder grips equipped with large self-sharpening universal Hammers with M18 bolts.

5 INTERNAL COUNTER-FRAME

Mulching chamber with double metal frame to increase the strength and integrity of the machine.


EQUIPMENT

PTO 540 rpm / Linkage cat. 1 and 2N / Drive shaft with guard / Rear roller Ø140 mm with protected bearings / Fixed counter-blade.

TR27 F

Front-mounted multi-purpose
for tractors up to 105 HP,
working width up to 2 m

Thanks to the patented SSA system, the TR27F front-mounted multi-purpose flail mower provides excellent results on grass, woody material, straw, plant residues, shrubs and prunings and is ideal for the maintenance of fallow land and green areas. The hitch is positioned to enable front-mounting on the tractor.



	TR27F-140	TR27F-160	TR27F-180	TR27F-200
Working width (mm)	1400	1600	1800	2000
Transport width (mm)	1550	1750	1950	2150
Tractor power (HP)	40-105	45-105	55-105	55-105
Hammers (no.)	12	14	16	16
Belts (no.)	3	3	3	3
Roller diameter (mm)	140	140	140	140
Maximum cutting diameter (Ø cm)	6	6	6	6
Weight with mechanical side shift (Kg)	-	-	-	-
Weight with hydraulic side shift (Kg)	525	555	605	640

1 "SSA" MULCHING CHAMBER

Variable volume mulching chamber with manual control for adjustment of the inside mobile gate.

2 SIDE TRANSMISSION

Side transmission with narrow casing thanks to the use of new high-performance VBHP SPECIAL (V-Belt-High-Performance) distribution belts.

3 FRONT HITCH

The hitch is positioned to enable front-mounting on the tractor.

4 PROFESSIONAL ROTOR

Professional rotor with angled tool-holder grips equipped with large self-sharpening universal Hammers with M18 bolts.

5 INTERNAL COUNTER-FRAME

Mulching chamber with double metal frame to increase the strength and integrity of the machine.

EQUIPMENT

PTO 1000 rpm / Linkage cat. 1 and 2 / Drive shaft with guard / Rear roller Ø140 mm with protected bearings / Fixed counter-blade / Hydraulic side shift.


TR36

TR56 *

Multi-purpose flail mower for tractors up to 150 HP, working width up to 3,1 m

Thanks to the patented SSA system, the TR36 and TR56 multi-purpose flail mowers provide excellent results on grass, woody material, straw, plant residues, shrubs and prunings. They are also ideal for the maintenance of fallow land and green areas.

***TR56**
WITH REINFORCED FRAME
AND OVERSIZED GEARBOX
AND ROTOR



	TR36-160	TR36-180	TR36-200	TR36-220C	TR36-240C	TR56-280	TR56-310
Working width (mm)	1600	1800	2000	2200	2400	2800	3100
Transport width (mm)	1750	1950	2150	2350	2550	2950	3250
Tractor power (HP)	45-105	50-105	55-120	60-120	65-120	70-150	70-150
Hammers (no.)	14	16	16	20	20	24	28
Belts (no.)	4	4	4	4	4	5	5
Roller diameter (mm)	160	160	160	160	160	160	160
Maximum cutting diameter (Ø cm)	8	8	8	8	8	10	10
Weight (Kg)	695	740	775	825	865	985	1055

1 "SSA" MULCHING CHAMBER
Multi-purpose mulching chamber with variable volume; changing the position of the hood, 2 different types of work can be obtained.

2 INTERNAL COUNTER-FRAME
Mulching chamber with double metal frame to increase the strength and integrity of the machine.

3 REAR HOOD
Opening rear hood for easy maintenance.

4 REAR ROLLER
The self-cleaning rear roller has an automatic roller cleaning system, thanks to its position very close to the rotor.

EQUIPMENT
TR36: PTO 540 rpm / TR56: PTO 1000 rpm / Linkage cat. 2 / Drive shaft with guard / Rear roller Ø160 mm with protected bearings / Fixed counter-blade / Second additional counter-blade / Hydraulically side shift.


TR36 F

TR56 F *

Dual hitch multi-purpose flail mower for tractors up to 180 HP, working width up to 3,1 m

Thanks to the patented SSA system, the TR36F and TR56F multi-purpose flail mowers provide excellent results on grass, woody material, straw, plant residues, shrubs and prunings. The dual three-point hitches enable these models to be mounted at both the front and the rear of the tractor. They are also ideal for the maintenance of fallow land and green areas.

***TR56 F**
WITH REINFORCED FRAME
AND OVERSIZED GEARBOX
AND ROTOR



	TR36F-180	TR36F-200	TR36F-220	TR36F-240	TR56F-280	TR56F-310
Working width (mm)	1800	2000	2200	2400	2800	3100
Transport width (mm)	1950	2150	2350	2550	2950	3250
Tractor power (HP)	55-150	60-150	65-150	70-150	75-180	80-180
Hammers (no.)	16	16	20	20	24	28
Belts (no.)	4	4	4	4	5	5
Roller diameter (mm)	160	160	160	160	160	160
Maximum cutting diameter (Ø cm)	8	8	8	8	10	10
Weight (Kg)	800	890	980	1020	1140	1210

1 "SSA" MULCHING CHAMBER
Multi-purpose mulching chamber with variable volume; changing the position of the hood, 2 different types of work can be obtained.

2 INTERNAL COUNTER-FRAME
Mulching chamber with double metal frame to increase the strength and integrity of the machine.

3 DOUBLE HITCH
Double 3-point hitch for front and rear machine applications.

4 REAR ROLLER
The self-cleaning rear roller has an automatic roller cleaning system, thanks to its position very close to the rotor.

5 REAR HOOD
Opening rear hood for easy maintenance.

EQUIPMENT
PTO 1000 rpm / Linkage cat. 2 / Drive shaft with guard / Rear roller Ø160 mm with protected bearings / Fixed counter-blade / Second additional counter-blade / Hydraulic side shift / Front chain guards (TR56F only).

TRILAT

Range of lateral flail mowers

Multi-purpose lateral flail mowers suited for working to the rear or side of the tractor and recommended for grass, plant residues, bushes and prunings with diameters up to 10 cm. Ideal for clearing green areas, gardens, roadsides, ditches, embankments, hedges and sloping land



HYDRAULIC SHOCK ABSORBER

The hydraulic system makes the machine self-levelling and shock-dampened on the tilting axis, making it easier to use with obstacles or particular soil conditions. It also protects the whole machine structure, dampening the shocks produced during work.




SELF-CLEANING REAR ROLLER

The self-cleaning rear roller has an automatic roller cleaning system, thanks to its position very close to the rotor.



ELASTIC ANTI-SHOCK SAFETY SYSTEM

“NO-STOP” elastic anti-shock safety system, the system is enabled when there are hidden obstacles, blocking the mulching chamber and dampening the shock.





INTERNAL COUNTER-FRAME

The mulching chamber, consisting of a double metal frame, increases the strength and integrity of the machine, while protecting the rear hood against damage.

EXTENDED HYDRAULIC SIDE SHIFT

The side shift has been maximised by the special frame structure, which ensures greater width of movement for the drive shaft.



TL31

	TL31 160	TL31 180	TL31 200	TL31 220
A (mm)	1600	1800	2000	2200
B (mm)	1820	1860	1860	1860
C (mm)	770	770	770	770
D (mm)	2350	2550	2750	2950
E (mm)	930	1130	1330	1530
F (mm)	1700	1700	1700	1700

TL33

	TL33 160	TL33 180	TL33 200	TL33 220
A (mm)	1600	1800	2000	2200
B (mm)	1820	1860	1860	1860
C (mm)	580	580	580	580
D (mm)	2540	2740	2940	3140
E (mm)	1100	1300	1500	1700
F (mm)	1700	1700	1700	1700

TL50

	TL50 200	TL50 220	TL50 240	TL50 260
A (mm)	2000	2213	2415	2600
B (mm)	2004	2004	2004	2004
C (mm)	589	589	589	589
D (mm)	3156	3369	3571	3756
E1 (mm)	1509	1722	1924	2109
E2 (mm)	1332	1545	1747	1932
E3 (mm)	1062	1275	1477	1662
F (mm)	2125	2125	2125	2125

TL31

Lateral flail mower
for tractors up to 130 HP,
working width up to 2.2 m

The TL31 multi-purpose lateral flail mower is able to operate both behind the tractor between rows and beside the tractor. It is recommended for grass, crop residues and prunings, on slopes, and for clearing orchards and vineyards, embankments and roadsides.

GEARBOX INTERNALLY
POSITIONED



IDEAL FOR
NARROW
SPACES

NO-STOP ELASTIC ANTI-SHOCK
SYSTEM

REAR
ROLLER

1 SIDE SHIFT

2 INTERNAL COUNTER-FRAME

3 HYDRAULIC
SHOCK ABSORBER



	TL31-160	TL31-180	TL31-200	TL31-220
Working width (mm)	1600	1800	2000	2200
Transport width (mm)	1800	2000	2200	2200
Tractor power (HP)	55-130	65-130	75-130	75-130
Hammers (no.)	14	16	16	18
Belts (no.)	4	4	4	4
Roller diameter (Ø)	140	140	140	140
Maximum cutting diameter (Ø cm)	8	8	8	8
Weight (Kg)	740	750	790	855

N.B.: Weight includes double homokinetic drive shaft.

TL33

Lateral flail mower
for tractors up to 130 HP,
working width up to 2.2 m

The TL33 multi-purpose lateral flail mower is able to operate both behind the tractor between rows and beside the tractor. This model has increased side-shift thanks to an externally mounted gearbox. It is recommended for grass, plant residues, shrubs and prunings, on slopes, and for clearing embankments and roadsides.

GEARBOX EXTERNALLY
POSITIONED



EXTENDED SIDE
SHIFT


NO-STOP ELASTIC ANTI-SHOCK
SYSTEM

REAR
ROLLER

1 SIDE SHIFT

2 INTERNAL COUNTER-FRAME

3 HYDRAULIC
SHOCK ABSORBER



	TL33-160	TL33-180	TL33-200	TL33-220
Working width (mm)	1600	1800	2000	2200
Transport width (mm)	2100	2300	2500	2700
Tractor power (HP)	55-130	65-130	75-130	75-130
Hammers (no.)	14	16	16	18
Belts (no.)	4	4	4	4
Roller diameter (Ø)	140	140	140	140
Maximum cutting diameter (Ø cm)	8	8	8	8
Weight (Kg)	760	790	810	850

N.B.: Weight includes double homokinetic drive shaft.

1 SIDE SHIFT
Extended hydraulic side shift.

2 INTERNAL COUNTER-FRAME
Mulching chamber with double metal frame to increase the strength and integrity of the machine.

3 HYDRAULIC SHOCK ABSORBER
System that protects the machine structure, dampening the shocks produced during work.

4 NO-STOP ELASTIC ANTI-SHOCK SYSTEM
Elastic anti-shock safety system enabled when there are hidden obstacles, blocking the mulching chamber and dampening the shock.

5 REAR ROLLER
The self-cleaning rear roller has an automatic roller cleaning system, thanks to its position very close to the rotor.

EQUIPMENT
PTO 540 rpm / Linkage cat. 2, fork-shaped / Drive shaft with guard or double homokinetic universal joint (choice of two) / Rear roller Ø140 mm with protected bearings / Fixed counter-blade / Pair of skids.

1 SIDE SHIFT
Extended hydraulic side shift.

2 INTERNAL COUNTER-FRAME
Mulching chamber with double metal frame to increase the strength and integrity of the machine.

3 HYDRAULIC SHOCK ABSORBER
System that protects the machine structure, dampening the shocks produced during work.

4 NO-STOP ELASTIC ANTI-SHOCK SYSTEM
Hydraulic safety system enabled when there are hidden obstacles, blocking the mulching chamber and dampening the shock.

5 REAR ROLLER
The self-cleaning rear roller has an automatic roller cleaning system, thanks to its position very close to the rotor.

EQUIPMENT
PTO 540 rpm / Linkage cat. 2, fork-shaped / Drive shaft with guard or double homokinetic universal joint (choice of two) / Rear roller Ø140 mm with protected bearings / Fixed counter-blade / Pair of skids.


TL50

Lateral flail mower
for tractors up to 220 HP,
working width up to 2.6 m

The TL50 multi-purpose lateral flail mower is suitable for professional use and is able to operate both behind and beside the tractor. This model has long side-shift thanks to an externally mounted gearbox. It is recommended for grass, plant residues, shrubs and prunings, on slopes, and for clearing large green areas, fallow land, ditches, embankments and roadsides.

Lateral flail mower
TriLat TL50


GEARBOX EXTERNALLY
POSITIONED



EXTENDED SIDE
SHIFT

NO-STOP ELASTIC ANTI-SHOCK
SYSTEM

WIDE HYDRAULIC TILTING



	TL50-200	TL50-220	TL50-240	TL50-260
Working width (mm)	2000	2200	2400	2600
Transport width (mm)	2527	2740	2972	3157
Tractor power (HP)	100-220	100-220	100-220	100-220
Hammers (no.)	16	20	20	22
Belts (no.)	5	5	5	5
Roller diameter (Ø)	160	160	160	160
Maximum cutting diameter (Ø cm)	10	10	10	10
Weight (Kg)	1165	1210	1240	1280

N.B.: Weight includes double homokinetic drive shaft.

- 1 SIDE SHIFT**

Extended hydraulic side shift, one of the largest in its category, with guaranteed safe positioning of the wheels on the tread.
- 2 INTERNAL COUNTER-FRAME**

Mulching chamber with double metal frame to increase the strength and integrity of the machine.

- 3 HYDRAULIC SHOCK ABSORBER**

System that protects the machine structure, dampening the shocks produced during work.
- 4 NO-STOP ELASTIC ANTI-SHOCK SYSTEM**

Hydraulic safety system enabled when there are hidden obstacles, blocking the mulching chamber and dampening the shock.

- 5 WIDE HYDRAULIC TILTING**

Wide hydraulic tilting (+90° / - 65°) to guarantee the safe maintenance of embankments and hedges.
- EQUIPMENT**

PTO 540 rpm / Linkage cat. 3, fork-shaped / Drive shaft with double homokinetic universal joint / Rear roller Ø160 mm with protected bearings / Fixed counter-blade / Pair of skids.



TRISTOC

Shredder range

Alpego heavy-duty shredders are ideal for shredding and chopping in open fields: bushes, straw, corn stalks, soy, crop residues, woody and organic materials found on fallow land.

TT97

The TT97 shredder features a rugged, reinforced double frame, ideal for chopping and shredding bushes, straw, corn and soybean stalks, crop residues, or woody or organic material on fallow land.

DEPTH CONTROL CHOOSE FROM:




SKIDS Pair of side skids.




PAIR OF WHEELS Pair of rear steering wheels.



REAR ROLLER Rear roller mounted on protected bearings.




INTERNAL COUNTER-FRAME The mulching chamber, consisting of a double metal frame, increases the strength and integrity of the machine, while protecting the rear hood against damage.



MONOCOQUE FRAME One-piece frame with no visible welds or joints, with no jutting parts. The rotor supports are protected and positioned inside.

Shredder for tractors up to 160 HP, and working width up to 3.2 m



	TT97-280	TT97-300	TT97-320
Working width (mm)	2800	3000	3200
Transport width (mm)	3000	3200	3400
Tractor power (HP)	80-160	90-160	100-160
Hammers (no.)	30	32	34
Flails (no.)	60	64	68
Belts (no.)	5	5	5
Roller diameter (Ø)	220	220	220
Weight (Kg)	1165	1235	1265

N.B.: Weight includes depth control

1 FRAME WITH NO JUTTING PARTS
One-piece frame with no visible welds or joints, with no jutting parts.

2 FIRST COUNTER-BLADE
First counter-blade built into the frame.

3 HAMMER OR FLAIL ROTOR
Tristoc shredders are available with rotor equipped with flails or hammers (CHOOSE WHICH).

4 PROVISION FOR SHIELD
Provision for internal anti-wear shield (available in the accessories).

5 REAR HOOD
Opening rear hood for easy maintenance.

EQUIPMENT
PTO 1000 rpm / Linkage cat. 2 / Drive shaft with guard / Side plates / Depth control (choose which).

Choosing the accessory

The right accessory for every situation



PAIR OF REAR STEERING WHEELS



REAR RAKE KIT



FRONT PROTECTION CHAIN KIT



DOUBLE HOMOKINETIC DRIVE SHAFT



COUNTER-BLADE KIT



ANTI-WEAR SHIELD FOR FRAME



SKIDS



DOUBLE HITCH KIT

Accessories	TB2	TR27	TR27F	TR36	TR36F	TR56	TR56F	TL50	TL31	TL33	TT97
Pair of rear steering wheels											
Rear rake kit											
Front protection chain kit											
Double homokinetic drive shaft											
Counter-blade kit											
Anti-wear shield for frame											
Skids											
Double hitch kit											



FOLDABLE POWER HARROWS

120 - 500 HP



RIGID POWER HARROWS

35 - 320 HP



SUBSOILERS

75 - 500 HP



ROTARY TILLERS AND STONE BURIERS

75 - 500 HP



SEED DRILLS

75 - 320 HP



FRONT HOPPERS

120 - 500 HP



CULTIVATORS

120 - 300 HP



FLAIL MOWERS

40-220 HP



ALPEGO